



## 2-group

Slayer Steam<sup>EP</sup>, the entry-level commercial Slayer, compares favorably to most espresso machine manufacturers' premier products. The new Steam<sup>EP</sup> is designed for fluid, simple operation while featuring high-end extraction capability. It fits multi-unit retailers, wholesale coffee providers and other equipment dealers and distributors, and retailers wanting to move up to the premium espresso machine range.

### **Classic 9-Bar Extraction with Pre-Wetting Control**

Volumetric brewing with programmable pre-wet from 0-4 seconds

### **Four Volume Settings Per Group**

Each button can be programmed to hold two volumetric presets, four settings per group.

### **Individual Brew Tanks with PID Temperature Control**

Consistent and reliable performance, ideal for high-volume beverage service

### **Push Button Actuation**

For fast programming and easy operation

### **Centralized, Heads-up Barista Dashboard**

Easy to operate and program volumetrics, temperature, pre-wet and more

### **Password Protection of Deeper Programming**

Give appropriate levels of control to baristas

### **Unique Design**

Soft-touch handles, powder coated wings and anodized aluminum panels



## Essential Features

- Volumetric activation, two buttons with four programmable settings
- Programmable pre-wetting 0-4 sec, per setting, four per group
- Centralized heads-up Barista Dashboard™
- Intuitive, password-protected menus
- Soft-touch steam actuators and portafilters
- PID-controlled independent brew tanks
- Hot water mix valve
- Massive work surface
- Wing channels keep wires and hoses hidden
- Anodized aluminum finish, body color
- Powder coated matte black wings

## Specifications

- Width: 34 inches / 86.5 centimeters
- Length: 27.75 inches / 70.5 centimeters
- Height: 16.75 inches / 42.5 centimeters
- Weight: 220 pounds / 100 kilograms (tanks filled)
- Brew tanks: 1.7 liters, 600 watts
- Steam tank: 7.4 liters, 3,500 watts
- Single-phase power: 200-260 volts AC, 50/60 hertz, 26 amps
- Three-phase power (optional): 380-400 volts AC, 50/60 hertz, 17 amps
- Wattage: 4,700 watts



Only available in anodized aluminum finish body color

